

QUICK DISCONNECT CHARGE FITTING SELECTION CHART

HYSON



Gas Spring Model		Quick Disconnect Charge Fitting
T2-50	T2SL-170	T2-770-T3 (M6 side or base port)
T2-90	T3-170	
T2-180	T3-320	
TNK 200	T3-350	
T2SC-420	T3-500	
T2SC-740	T3-750	
T2L-300	T3-1000	
T2SS-16	T3-1500	
T2SS2-16	T3-2400	



Gas Spring Model		Quick Disconnect Charge Fitting
NP-750	T2SLM-300	T2-770-G1/8-P (BSPP 1/8 port)
NP-1500	T3-4200	
NP-3000	T3-6600	
NP-5000	T3-9500	
NP-7500	LCF-3000	
T2SC-1800	LCF-5000	
T2SC-2900	LCF-7500	
T2SC-4700	CS2-1500	
T2SC-7500	CS2-3000	
T2SC-11800	CS2-5000	
T2SC-18300	CS2-7500	



Gas Spring Model		Quick Disconnect Charge Fitting
TNK 1		T2-770-4 (7/16"-20 port)
T2L-500		
T2L-750		
T2L-1500		
T2L-3000		
T2L-5000		
T2-750P		
T2B-1500		
T2B-3000		
T2B-5000		
T2-7500		



Gas Spring Model		Quick Disconnect Charge Fitting
T2LS-250		T2-770-M6 (M6 rod port)
T2LS-300		
T2LS-500		
T2LS-750		
T2SC-1000		



Gas Spring Model		Quick Disconnect Charge Fitting
TNK 400		11-770-0705 MTY (3/8"-32 port)
TNK 400HS		



Gas Spring Model		Quick Disconnect Charge Fitting
TNK 3		T2-770-4-L (7/16"-20 port)
TNK 5.5		
TNK 9		

For Control Panels, Pressure Monitors and other accessories



11-770-2700
(1/4" NPT Female)



11-700-8555
(1/2"-20 O Ring)



11-770-0705
(1/4" NPT Male)

Hyson® Products

Associated Spring

10367 Brecksville Road • Brecksville, OH 44141 USA
Toll Free: 1-800-876-4976 • Tel: 440-526-5900 • Fax: 440-838-7684
www.hysonproducts.com • Email: hyson@asbg.com

Notes: The charge fitting is needed only when charging self-contained gas springs. It is not needed for a hoses or baseplate system.

Check individual product catalogs for minimum and maximum charging pressures.



© Hyson Products 2005
CFC2M1005